



LAVE-VAISSELLE 500U AVEC POMPE DE VIDANGE

- châssis et paroi Acier Inox AISI 18/10
- Bras de lavage et de rinçage Acier inox
- Contact de sécurité-porte
- Porte double paroi
- Panier 500 x 500 mm
- Résistance de cuve et surchauffeur Incoly 800
- Alimentation électrique 230 V 50Hz
- Résistance de la cuve 2 600 W
- Résistance du surchauffeur 2 500 W
- Consommation d'eau 2 litres
- Contenance de la cuve 24 litres
- Doseurs électriques réglables de détergent et de produit de rinçage
- Raccord pour l'eau G3/4M
- Écoulement Ø 25 mm
- Rendement 30 casiers par heure
- Durée de cycle 120 secondes
- Dotation 2 paniers 500 x 500 mm, porte-couverts
- Puissance 3 120 W / 230 V
- Dimensions L 585 x P 600 x H 815 mm
- Poids 56 Kg

Référence article : CLVA50UPV
EAN : 3611630083683

DISHWASHER 500U WITH DRAIN PUMP

- Frame and wall AISI 18/10 stainless steel
- Washing and rinsing arms Stainless steel
- Door safety contact
- Double-walled door
- Basket 500 x 500 mm
- Tank heater and superheater Incoly 800
- Power supply 230 V 50 Hz
- Tank heater 2.600 W
- Superheater resistance 2.500 W
- Water consumption 2 liters
- Tank capacity 24 liters
- Adjustable electric detergent and rinse aid dosing units
- Water connection G3/4M
- Outlet Ø 25 mm
- Output 30 baskets per hour
- Cycle time 120 seconds
- 2 baskets 500 x 500 mm, cutlery holder
- Power 3 120 W / 230 V
- Dimensions W 585 x D 600 x H 815 mm
- Weight 56 kg

Article reference : CLVA50UPV
EAN : 3611630083683